

RS6D-P

215/220/225/230/235P

All-Purpose Module

RS6D is a robust solar module with 54 solar cells. These modules can be used for on-grid solar applications. Our meticulous design and production techniques ensure a high-yield, long-term performance for every module produced. Our rigorous quality control and in-house testing facilities guarantee Resun Solar's modules meet the highest quality standards possible.

Polycrystalline Silicon Solar Modules

Features



High module conversion efficiency (up to 15.98%), through superior manufacturing technology



Guaranteed 0- +5W positive power output tolerance ensures high reliability



Anti-reflective, hydrophobic coating improves light absorption and reduces surface dust



Excellent performance under low light environments (mornings, evenings and cloudy days)



Entire module certified to withstand high wind loads (2400 Pascal) and snow loads (5400 Pascal)*




All-purpose Module

Sales network covers more than 50 countries, providing customers with instant after sales service and an efficient supply-chain, our clients can be found throughout the world, such as North America, Europe, Oceania, Eastern Europe, East Asia, Middle Easter and Africa etc. Resun Solar team works closely with our customers to provide them with solutions for all their solar needs.



Resun reputation is founded on more than 300MW of high performance solar modules installed around the world.

Industry-leading warranty




- 25 year transferable power output warranty:10year/90%;25year/80%.
- Based on nominal power.
- 10 year material and workmanship warranty.

RS6D-P

215/220/225/230/235P


Electrical Data



STC	RS6D 215P	RS6D 220P	RS6D 225P	RS6D 230P	RS6D 235P
Nominal Maximum Power(Pmax)	215W	220W	225W	230W	235W
Optimum Operating Voltage(Vmp)	27.4V	27.6V	27.7V	27.9V	28.1V
Optimum Operating Current(Imp)	7.85A	7.98A	8.12A	8.24A	8.36A
Open CIRCUIT voltage(Voc)	33.5V	33.7V	33.8V	34.0V	34.3V
Short Circuit Current(Isc)	8.44A	8.58A	8.79A	8.92A	9.05A
Module Efficiency	14.62%	14.96%	15.30%	15.66%	15.98%
Operating Temperature	-40℃~+85℃				
Maximum System Voltage	1000V(IEC)/600V(UL)				
Maximum Series Fuse Rating	15A				
Application Classification	Class A				
Power Tolerance	0 ~ + 5W				

IV-Curves

Under Standard Test Conditions (STC) of irradiance of 1000W/m², spectrum AM 1.5 and cell temperature of 25℃



Mechanical Data

Cell Type	Poly-crystalline 156 x 156mm,3 or 4 Bus bars
Cell Arrangement	54 (6x9)
Dimensions	1482 x 992 x 40mm(58.35 x 39.06 x 1.57in)
Weight	18kg
Front Cover	3.2mm Tempered Glass
Frame Material	Anodized Aluminum Alloy
J-BOX	IP65 or IP67, 6 Diodes
Cable	4mm2(IEC)/12AWG(UL),1150mm
Connectors	MC4 or MC4 Comparable
Standard Packaging (Modules per Pallet)	27pcs
Module Pieces per container (40HQ)	616pcs (40'HQ)

Temperature Characteristics

Nominal Operating Cell Temperature (NOCT)	45±2℃
Temperature Coefficient of Pmax	-0.45%/℃
Temperature Coefficient of Voc	-0.34%/℃
Temperature Coefficient of Isc	0.05%/℃

Packing Configuration

Container	20'GP	40'HQ
Pieces	240	616

Resun Solar Energy Co.,Ltd

Add:No 15 Puzhuang Avenue,Wuzhong District,Suzhou, Jiangsu China.

Tel: +86 0512 66292101

Fax: +86 0512 66293858

E-mail: info@resunsolar.com

http://www.resunsolar.com